

MATERIAL SAFETY DATA SHEET

SECTION 1 - SOURCE/IDENTITY/USE INFORMATION**MANUFACTURER**

GC AMERICA INC.

3737 West 127th St.

Alsip, Illinois, 60803

Telephone: 708-597-0900

Hours: Mon.- Fri. 8:00 am. - 5:00 pm. C.S.T.

Transportation Emergency Telephone No. 800-424-9300

COMMON NAME: NATURE-CRYL MC LIQUID**Chemical Name:** N.A.**PRODUCT USE:** Construction of dental prosthesis - liquid component.

The following information is provided with regard to the toxicity and hazards of the pure components present in this portion of the unmixed powder/liquid system.

SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

COMPONENT	C.A.S.	EXPOSURE LIMITS	LD50/LC50	%
Methyl methacrylate	80-62-6	TWA=100ppm (ACGIH)	LD50=7.9g/kg (oral rat) LC50=3750 ppm/4hr	90-95

SECTION 3 - PHYSICAL/CHEMICAL PROPERTIES

BOILING POINT: 99°C **SPECIFIC GRAVITY (H₂O = 1):** 0.9
VAPOR PRESSURE: 29mm @20°C **MELTING POINT:** -48°C
VAPOR DENSITY (Air=1.0): 3.46 **EVAPORATION RATE(Butyl Acetate=1):** Equal
SOLUBILITY IN WATER: 1.7% **ODOR THRESHOLD:** <1ppm Methyl methacrylate
COEFFICIENT OF OIL/WATER DISTRIBUTION: N.E. **APPEARANCE AND ODOR:** Clear liquid, unpleasant odor

SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT: 12.8°C/55°F (Open cup) **FLAMMABLE LIMITS:** LEL = 1.7 UEL=8.2
EXTINGUISHING MEDIA: Alcohol foam, dry chemical, carbon dioxide
SPECIAL FIRE FIGHTING PROCEDURES: Wear self contained breathing apparatus with full protective equipment.
UNUSUAL FIRE AND EXPLOSION HAZARDS: When heated above the flashpoint: emits vapors, which when mixed with air, can burn or be explosive. Fine mists on sprays may be flammable at temperatures below the flash point. Sealed containers exposed to elevated temperatures may rupture explosively due to polymerization. Vapors are heavier than air and may travel to ignition source.
HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, carbon monoxide, smoke.

SECTION 5 - REACTIVITY DATA

STABILITY: **Stable** **Unstable**
Polymerization: **Will Not Occur** **Will Occur**

CONDITIONS TO AVOID: Heat and ignition sources.**INCOMPATIBILITY (Materials to Avoid):** Reducing and oxidizing agents. Material has strong solvent properties and can soften paint or rubber.**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** None known**SECTION 6 - HEALTH HAZARD DATA and FIRST AID INFORMATION**

	YES	NO	NE	NA	NTP	IARC	OSHA	OTHER

MUTAGENIC AFFECTS		X						
TERATOGENIC AFFECTS		X						
REPRODUCTIVE TOXIN		X						
CARCINOGENICITY		X						
SENSITIZER	X							

ROUTES OF ENTRY: **Inhalation** **Skin** **Ingestion**

HEALTH HAZARD (Acute and Chronic): Inhalation may cause nose and throat irritation. May cause nervous system depression. Reports have associated repeated and prolonged overexposure to brain damage and nervous system damage. May cause irritation or burning of eyes, skin, and mucous membranes. Repeated exposure may cause skin burns and allergic reactions. May cause abnormal liver and kidney function.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Progressive steps of inhalation overexposure: headache, dizziness, nausea, staggering gait, confusion, unconsciousness.

CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N.A.

EMERGENCY FIRST AID PROCEDURES:

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

EYE CONTACT: Immediately flush eyes with water. Seek medical attention.

SKIN CONTACT: Wash affected area with soap and water. Wash clothes prior to reuse.

INGESTION: Do not induce vomiting. Give one or two glasses of water and refer to medical attention.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

IN CASE OF RELEASE OR SPILL: Eliminate source of ignition. Wear skin, eye, respiratory protection. Contain spill and keep out of sewers. Use absorbent to soak up liquid. Use non-sparking equipment and shovel into waste container.

WASTE DISPOSAL METHOD: Material is a hazardous waste, No. U162. Dispose of waste in facility permitted for hazardous waste in accordance with local, state and federal regulations.

STORAGE, HANDLING, AND SPECIAL PRECAUTIONS: Keep away from heat, sparks, flame, direct sunlight and elevated temperatures.

SECTION 8 - CONTROL MEASURES

RESPIRATORY PROTECTION: Reduce exposure in accordance with safe hygiene practice. If exposure limits are exceeded, use an MSHA-NIOSH approved respirator for organic vapors.

VENTILATION: **Local Exhaust:** X **Mechanical:** N.A. **Special:** N.A. **Other:** N.A.

PROTECTIVE GLOVES: Disposable Vinyl Gloves

EYE PROTECTION: Chemical eye goggles and full face protection if necessary.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Eye wash station

WORK/HYGIENIC PRACTICE: Follow routine safe hygiene practices

SECTION 9 - PREPARATION INFORMATION

This data is supplied to comply with OSHA Hazard Communication Standard 29 CFR 1910,1200 and W.H.M.I.S. CPR

PREPARED BY: T. Joritz _____ **Date:** 01 March 2006 _____
Director, Regulatory Affairs

N.A. = NOT APPLICABLE

N.E. = NOT ESTABLISHED

The information herein is given in good faith but no warranty expressed or implied is made.

FIRE – 4

TOXICITY – 2

NFPA
REACTIVITY – 3

SPECIAL – P

